

The Standard for Quality!

A detailed look at a Mac-Lander Trailer reveals the solid construction inside and out. Mac-Lander incorporates the highest quality materials, workmanship and unique features to build the trailers that set the standard for quality.



Mac-Lander Features

- · Electric brakes on all axles
- · Wiring loom protected in conduit
- Solid gusset on enclosed fenders
- Frame cross members designed for increased strength
- · Safety brake-away kit with battery
- · Premium radial tires
- · Reliable sealed beam tail lights
- Fully primed and painted with acrylic enamel and hardner
- · Leaf spring suspension
- · 5 foot heavy duty ramps

- · Frames are Mig welded in fixtures
- · Rugged structural frame
- · Heavy duty safety chains
- · 2" pressure treated wood floors

Features that make a difference!



FM, FH & SL Series equipped with "Roughneck" diamond plated fenders.



All Mac-Lander trailers are equipped with conduit enclosed wiring loom and safety break-away kit with battery.



FH and SL Series equipped with heavy duty spring assist jack.



DO Series equipped with protected and recessed tail lights.



E-Z Crank Beavertail.



All tag-alongs equipped with reliable sealed beam tail lights.



Frame Heavy Series

12,000# GVWR or 14,000# GVWR with 7K drop axles, 16" radials, 8 bolt hubs, heavy duty jack, 6" channel frame and tongue.

Models: 20TFHWS 20TFHSB 20TFHWB 20GFHWS 20GFHSB 20GFHWB



Frame Standard Series

7,000# GVWR, 4"channel tongue, 15" radial tires.
Models: 16TFSWS 18TFSWS 18TFSWB 18TFSSB 18TFSSB



Deck Over Series

14,000# GVWR to 21,000# GVWR with 7K straight axles, available in tag along or goose neck. Features E-Z crank beavertail, tandem or triple axles, 16" radial tires, 8 bolt hubs.

Models: 25TDOWC 25GDOWM 29TTAWC 29GTAWC



Tandem Dual Series

25,900# GVWR, available in tag along or goose neck with straight deck or beavertail. Features 2 speed double drop leg landing gear jack, lengths of 25, 29 and 33 feet, oil bath bearings, 16" radial tires and fold-over ramps. Fabricated pierced flanged beam frame for low floor height.

Models: 25TTDWC 29TTDWC 33TTDWC 25GTDWC 29GTDWC 33GTDWC



Tandem Dual Heavy Series

32,000# GVWR, 25' tag type with 16K straight air brake axles, oil bath bearings, 2 speed double drop leg landing gear, 17.5" tires, fabricated pierced flanged beam frame with reinforced cross members and ramps.



Frame Medium Series

9,990# GVWR with 6K axles, 15" radials, 8 bolt hubs, 5" channel frame and tongue.

Models: 20TFMWS 20TFMWB 18TFMWS 18TFMWB 18TFMSB



20' Frame Heavy Tilt Bed

12,000# GVWR or 14,000# GVWR with 7K drop axles, 12 volt electric/hydraulic power system, 8 bolt hubs, heavy duty jack, 6" channel frame and tongue. Rear 16' tilts, front 4' stationary. 10° loading angle. Model: 20TFHWT



18' Frame Medium Tilt Bed

9,990# GVWR with 6K drop axles, 12 volt electric/hydraulic power system, 8 bolt hubs and heavy duty jack, 5" channel frame and tongue. Full 18' tilt. Low 20" floor height.







The benefits to our customers are trailers that set "The Standard for Quality"

CAD designed trailers · Mig Welding · Fixtured Manufacturing
Computerized Production Control · Computer Inventory Control
Rigid Quality Standards · Member NATM
All Trailers Meet or Exceed all NATM Guidelines
Comprehensive Operator's Manual · Extensive Parts Inventory
Factory Field Support · All Trailers Meet DOT Specs.

3yr Limited Warranty · National Dealer Network · Annual Newsletter

www.mac-lander.com





MATERIAL HANDLING EQUIPMENT

Dea	ler:

New Location!

509 E Maple - Milton IA 52570 (800) 346-1792 / (641) 656-4271 www.mac-lander.com

